

# ***Solution 7210***

## **(Boiler Water Treatment for Soft Water Make-up)**

- ◆ **High Level of Active Ingredients**
- ◆ **Buffered for pH Control**
- ◆ **Effective in Most Steam Boiler Systems**
- ◆ **Provides Superior Results**

***Solution 7210*** contains a blend of alkalinity builders / polymers and sulfite. This product is designed to be used where there is no condensate return as a single drum, “All Organic” treatment for low-pressure boilers.

### **TYPICAL PROPERTIES**

<b>Appearance</b>	<b>Clear Amber</b>
<b>pH</b>	<b>≥ 13 (undiluted)</b>
<b>Solubility</b>	<b>Complete</b>
<b>Specific gravity</b>	<b>1.11 – 1.12 (water = 1.0)</b>

### **USING PROCEDURES**

***Solution 7210*** should be controlled by a hydroxide alkalinity (P) level between 300 – 600 ppm. Sulfite Levels should be maintained between 30-60 ppm. Actual use rates will vary as determined by individual operating conditions and system requirements.

### **FEEDING**

***Solution 7210*** can be fed directly from the shipping container. Continuous feed by chemical pump in proportion to make-up is preferred.

### **STORAGE**

***Solution 7210*** should be stored in a dry place. Do not store at temperatures below 50°F. Recommended maximum storage limit is 1 year.

### **SAFETY**

Please refer to the product label and Material Safety Data Sheets for all warnings, recommendations and other regulatory information. Copies of the Material Safety Data Sheets are available from the Win Solutions office or your local representative.

***Win Solutions, Inc.***  
***109 Pine Street***  
***Lexa, AR 72355***  
***PH 800-489-0470***  
***www.solutionswin.com***